

INSTALLATION INSTRUCTIONS

Please read these instructions carefully before proceeding. We strongly recommend that this product is installed by a qualified plumber.

This WC must be installed with a concealed cistern. Please refer to the cistern manufacturer's instructions. Ensure that the cistern is fully commissioned and that there are no leaks before concealing.

Check the product for any transport damage before proceeding. Check that all components for the floor fixings are present according to the information printed on the bag. It is recommended that the WC pan is first positioned in the desired installation area, and its final position marked faintly with a pencil. This is to ensure that the pan can be positioned easily and all necessary fittings are to hand.

1. Position the pan in the desired location and lightly mark a centre line on the floor corresponding with the holes at the base of the pan for the floor fixings. Measure the inside profile of the base of the pan to ensure that the floor fixings are positioned correctly, in order to determine Dimension X and Y. Secure the floor fixing brackets in the correct place using the fixings provided. Ensure that the flush pipe is trimmed to the correct length to fit into the inlet of the pan.
2. Connect the cistern flush pipe into the back of the pan and connect the waste pipe with an appropriate connector for the installation in hand, before aligning the pan with the fixing brackets on the floor. It is important that the fixing brackets are in the correct position and that the pan fits flush with the finished wall or furniture surface.
3. Secure the pan to the floor fixing brackets with the fixings provided.

Once installed, flush test the WC pan, checking for any leaks before sealing the pan to the finished surface with a bead of silicone.

DIMENSIONS

