

Cohort Cross Tall Basin Mixer with Click Waste

TCC50 (Chrome), TCC5004 (Brushed Brass), TCC5005 (Gunmetal)




FLOW RATE DATA IS TESTED UNDER
LABORATORY CONDITIONS: ACTUAL
FLOW RATE MAY VARY DEPENDING ON
DOMESTIC SUPPLY AND ACCESSORIES

Minimum Pressure:	0.5 BAR
Pressure:	Flow Rate (l/min)
0.5 BAR	4.25
1 BAR	5.5
2 BAR	7.91
3 BAR	9.8

Dimensions

Diagrams not to scale. All dimensions in mm (tolerance of +/-5mm)



FAQs

- What connections do the flexible hoses have?** This tap uses flexible hoses with 1/2" BSP captive nut connections.
- What size Pipework do i need?** It is recommended to use 15mm with G1/2" plumbing fittings.
- What is the recommended operating pressure?** 0.5 BAR.
- How do I care for the finish on this tap?** We recommend using only a damp cloth and warm water. Do NOT use abrasive cleaning products or cleaning chemicals as this may damage the surface of the product.
- Is the supplied click waste suitable for use with a vessel basin?** Yes, the waste can be used with vessel basins with and without an integrated overflow.