TECHNICAL DATA SHEET

ROPER RHODES®

WIZ LED KIT — WIZLEDKIT-450, WIZLEDKIT-750

BOX CONTENTS:

1 x LED Strip IP65 (450 or 750mm long), 1 x Driver Box, 1 x Fixing Kit Bag

FAQ's

| | Units | WIZLEDKIT-450 | WIZLEDKIT-750 | | | | |
|--|-------|--|---------------|--|--|--|--|
| Where is the Light Switch located? | - | The LED lights can be controlled by the Wiz App or by using a Smart Wiz Button to be purchased separately. | | | | | |
| What are the dimensions of the Driver Box? | mm | 140 x 105 x 46 | | | | | |
| Where is the reset button located? | - | On the WIZ-DRIVER box side, next to the cable to connect LED Strip | | | | | |
| What is the LED Strip Length? | mm | 450 | 750 | | | | |
| Can the LED lighting be replaced? | = | No | | | | | |
| Is the LED Kit supplied with mains cable? | | Kits are supplied with a removeable 500mm mains cable | | | | | |

For further FAQ's related to Wiz App go to: https://www.roperrhodes.co.uk/smart-lighting

ELECTRICAL SPECIFICATION

| | Input Voltage | Lamp Type | LEDs (W) | LED (lm) | Energy Rating | CCT (K) | CRI | IP Rating | Electrical Class |
|---------------|---------------|-----------------|-------------|-------------|------------------|------------|-----|--------------|---------------------|
| WIZLEDKIT-450 | 220-240V 50Hz | 12V DC LED Lamp | 4.59 | 504 | F | 3000-6000 | 80 | IP65 | Class II |
| WIZLEDKIT-750 | 220-240V 50Hz | 12V DC LED Lamp | 7.88 | 864 | F | 3000-6000 | 80 | IP65 | Class II |

Please note:

- · Dimensions are subject to change. Customers are advised to measure actual product dimensions before commencing installation.
- The LED (Im) values represent the output of the LED. Actual product level Lumen output may vary depending on the diffuser material i.e., glass or acrylic.

ROPER RHODES®

TECHNICAL DRAWINGS

